



143 Gunnedah Road
P O Box 7090 NEMSC
Tamworth, NSW 2348
Australia

Ph: (02) 6755 6000
Fax: (02) 6755 6006
e: sales@monitor.net.au

MONITOR MACHINE INDUCTION

MODEL :

HILYTE H8200

Note : Operators of boom lifts over 11 metres platform height are required to hold an EWP WorkCover licence. For all other lifts, an EWPA Yellow Card is recommended.....

Warning! This is a basic induction only, and is not designed to remove the responsibility the operator has to be fully conversant with the Operator’s Manual and any site-specific requirements.....

Firstly : Read “Using Elevating Work Platforms Safely” handbook before operating the Hilyte.

INTRODUCTION:

- 1) Safety harnesses must be worn
- 2) Identify Safe Working Load (120kg, single person)
- 3) Height / weight limit features (if applicable)
- 4) Limit switches must not be tampered with
- 5) Identify Wind Load Rating on Compliance Plate
- 6) Identify swing and crush hazards
- 7) Logbook must be filled in daily
- 8) Operators manual for technical assistance
- 9) Personal protective clothing and / or equipment requirements.....

OPERATION: (Note: Perform pre-operation checks !)

- 1) Initial set-up: Select neutral gear, pull handbrake on, remove ignition key and lock vehicle.....
- 2) Stabilizer Legs: Ensure legs are deployed on firm ground
- 3) Level machine using level indicator
- 4) Use extreme caution on sloping terrain

- 5) Always use wheel chocks on uneven ground.....
- 6) Ensure Hilyte is secured correctly to the vehicle
(clamped down to loading-board bracket and pinned to tow-hitch)
- 7) Use ground controls to raise and rotate then lower boom

- 8) Assemble work platform, ensuring both pins are securely fitted.....
- 9) Switch to platform controls to operate from platform position.....

- 10) Boom operation: Levers and their functions
- 11) Duplicate controls at ground for emergency use
- 12) Emergency lowering system
- 13) Dangers of overhead power: non-insulated boom.....
- 14) Do not use as crane or tie items to platform.....
- 15) Boom must be completely down before raising stabilizers

- 16) Removing Hilyte from vehicle:
Follow steps closely in Operator's Manual.....

SERVICE:

- 1) Any faults or requirements must be immediately discussed w/- Monitor
before further operation

- 2) All E.W.P.'s must be serviced every 100 hours or 3 months by regulation.
Advise workshop if the machine reaches either of these intervals

OTHER:

- 1) Hirer's responsibilities (theft / damage)
- 2) Theft & Damage Waiver: reduces liability.....
- 3) Hire Contract Terms & Conditions.....
- 4) Monitor contact numbers for any assistance
- 5) Notes:

Date: ___ / ___ / ___

Location: _____

I acknowledge I have completed the above induction and fully understand each point covered.

Signature: _____

Name: _____

Ph: _____

Employer: _____

Ph: _____

Address: _____

Fax: _____

The above induction was given and completed by:

 Print Name

 Signature