



143 Gunnedah Road
P O Box 7090 NEMSC
Tamworth, NSW 2348
Australia

Ph: (02) 6755 6000
Fax: (02) 6755 6006
e: sales@monitor.net.au

MONITOR MACHINE INDUCTION

MODEL : C1 Mobile Crane

Warning! This is a basic induction only, and is not designed to remove the responsibility the operator has to be fully conversant with the Operator's Manual and any site-specific requirements.....

INTRODUCTION:

- 1) Identify Safe Working Load
- 2) Height / weight limit features/counterbalance weight (if applicable)
- 3) Limit switches must not be tampered with
- 4) Slope of area to be operated, must be less than 1% for pick and carry.....
- 5) Identify Wind Load or sail effect if applicable
- 6) Identify swing and crush hazards
- 7) **Extreme importance** of lifting loads by the load centre of gravity
- 8) Operators manual for technical assistance
- 9) Personal protective clothing and / or equipment requirements.....

OPERATION: (Note: Perform pre-operation checks!).....

- 1) Use caution on uneven ground.....
- 2) The use of wider track if needing to manoeuvre on uneven ground.....
- 3) Reverse up slopes without load
- 4) Do not leave parked on a slope.....
- 5) Always drive with wide track unless access is limited
- 6) Keep well clear of the machine when driving
- 7) Stay outside the exclusion zone from the machine when lifting loads
- 8) Never stand on the lower side of the machine on a slope.....
- 9) Check that the counterbalance weight is locked in the required position
- 10) Check the ground conditions for stability and friction, especially after rain and or earthworks.
- 11) Levers, Buttons and their functions
- 12) Emergency drive or brake release
- 13) Dangers of overhead power: non-insulated booms.....
- 14) Boom must be completely down or lowered as much as possible before manoeuvring machine

15) 240 volt Charging of batteries.....

TRAILER (if applicable):

- 1) Loading and unloading
- 2) Correct load balance
- 3) S.W.L. of towing vehicle
- 4) Brakes and adjustments
- 5) Safety chain connection
- 6) Correct tie-down method
- 7) Handbrake on in towing vehicle + remove keys and lock doors to prevent unauthorised access

SERVICE:

- 1) Any faults or requirements must be immediately discussed w/- Monitor before further operation
- 2) Flashing lights and movement alarms must not be disconnected. Report any malfunction immediately
The unit should be kept in full safe operating condition according to the operator's manual and any site-specific requirements

OTHER:

- 1) Hirer's responsibilities (theft / damage)
- 2) Theft & Damage Waiver: reduces liability.....
- 3) Hire Contract Terms & Conditions.....
- 4) Monitor contact numbers for any assistance
- 5) Notes:
